


# FOR ALL MAKES & MODELS ***FORK-ARMS***



[www.pandasolutionsllc.com](http://www.pandasolutionsllc.com)

Fully controlled process to make sure forks meet or exceed international standards regards to mounting details, load, fatigue and impact tests.

- **Robotic welding** to ensure better welding quality.
- **Two steps shot blast** provides better surface and good finish
- **Clear Stamping** at upright of shank with production date, Series No and Batch No.
- **Special treatment at the inside heel** removes the possible edges or other imperfections.
- **Pairing tolerance** strictly meet ISO2328/2330
- **Dye penetrant test** at the heel to guarantee no visual crack
- **Magnetic particle** inspection ensure no visual crack
- **Weld ultrasonic test** to guarantee no internal crack
- **Application test** to guarantee 3 times safety factor
- **Steel analyzing** to guarantee the qualified steel
- **Heel Guard design to double fork-arms lifetime.**



FOR ALL MAKES & MODELS  
***FORK-ARMS***



[www.pandasolutionsllc.com](http://www.pandasolutionsllc.com)

**Most popular size**

Fork size	Weight /ea (lb)	Capacity/pair @ 24"LC (lb)	Qty. in 20'GP (ea)
2A 1.375"x4"x42"	91.08	3740	420
2A 1.375"x4"x48"	100.10	3740	382
2A 1.50"x4"x42"	100.10	5060	382
2A 1.50"x4"x48"	110.44	5060	346
2A 1.75"x4"x42"	108.46	6160	352
2A 1.75"x4"x48"	120.12	6160	318
2A 1.75"x4"x60"	143.44	6160	266
3A 1.75"x4"x42"	120.34	6160	318
3A 1.75"x4"x48"	132.00	6160	290
3A 1.75"x4"x60"	155.32	6160	246
3A 1.75"x5"x42"	148.72	7700	256
3A 1.75"x5"x48"	163.24	7700	234
3A 1.75"x5"x60"	192.50	7700	198
3A 2" x 5" x 42"	163.68	9460	232
3A 2" x 5" x 48"	179.96	9460	212
3A 2" x 5" x 60"	212.30	9460	180
4A 2" x 6" x 48"	247.94	11440	154
4A 2" x 6" x 60"	286.66	11440	132
4A 2.5" x 6" x 48"	308.66	19360	124
4A 2.5" x 6" x 60"	359.26	19360	106
4A 2.5" x 6" x 72"	411.40	19360	92

- ◆ Cross section from 1"x2" to 5.5"x12.6", length from 24" to 150"
- ◆ Special forks are available. Such as Block forks, Tire & Barrel forks, shaft forks, lumber & plywood forks, fork extensions, carpet boom, folding forks, spark retardant forks and Coil handling forks etc.
- ◆ Customized forks are upon request.

Phone: 864-491-5380 ( Ext 201 / 102 )

Email: [sales@pandasolutionsllc.com](mailto:sales@pandasolutionsllc.com)